



Arak Petrochemical Company



ISO 9001:2000

Certificate No.: CH98/8032

ISO 14001:2004

Certificate No.: CH03/0112

OHSAS 18001:1999

Certificate No.: CH05/0675

## Triethylene glycol (TEG)❖

Characteristic	Test Method	Unit	Value
PURITY	ASTM E -202	WT.%	97 MIN.
MEG CONTENT	ASTM E -202	WT.%	2 MAX.
TEG CONTENT (T.TEG)	ASTM E -202	WT.%	1 MAX.
WATER	ASTM E -203	WT.%	0.05 MAX.
COLOR	ASTM D -1209	Pt-Co	25 MAX.
ACIDITY AS ACETIC ACID	ASTM D -1613	WT.%	0.01 MAX.
ASH	DC-254/A	PPM	50 MAX.
SP. GR (20/20 °C)	ASTM D- 891	-	1.124 - 1.126
DISTILLATION @ 760 MM-Hg			
5-95 VOL % RANGE	ASTM D-1078	°C	280-295

❖ Not exportable.

**TRIETHYLENEGLYCOL** obtained from the reaction of ethylene oxide and DEG. It is a clear, transparent and odorless liquid that can be mixed with water in any proportion.

### ○ **Application areas:**

#### • **Resins :**

**TRIETHYLENEGLYCOL** is used as a synthesizing agent for alkyd resins as well as saturated and unsaturated polyester.

#### • **Synthesizing agents :**

**TRIETHYLENEGLYCOL** can be used as synthesis intermediates.

**TRIETHYLENEGLYCOL** esters with fatty acids (oleic, stearic, lauric, etc.) are used as emulsifiers and plasticizers of polymers.

#### • **Brake fluids :**

**TRIETHYLENEGLYCOL** can be used as secondary solvent in brake fluid formulations. This product is also used to avoid the excessive swelling of rubber in the hydraulic system.

#### • **Other uses :**

**Ethyleneglycols** can also be used in the formulation of printing ink, in the treatment of gases, in the formulation of fire-resistant hydraulic fluids, in the formulation of cutting oils, in the formulation of surface polishers, in the formulations of agrochemicals, in the extraction of solvents, in the manufacture of pigmented pastes and putty for walls, and in the synthesis of explosives.

### ○ **Storage conditions :**

Under nitrogen blanket and at ambient temperature.

### ○ **Packing :**

Bulk or in 220 Lit (net: 220 Kg) new drums, each 4 drums strapped on a pallet.