



Health	2
Fire	3
Reactivity	0
Personal Protection	H

Material Safety Data Sheet

Isobutyl alcohol MSDS

Section 1: Chemical Product and Company Identification

Product Name: Isobutyl alcohol

Catalog Codes: SLB2980

CAS#: 78-83-1

RTECS: NP9625000

TSCA: TSCA 8(b) inventory: Isobutyl alcohol

CI#: Not applicable.

Synonym: Isobutanol; Iso-Butyl Alcohol

Chemical Name: 2-Methyl-1-propanol

Chemical Formula: (CH₃)₂CHCH₂OH

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Isobutyl alcohol	78-83-1	100

Toxicological Data on Ingredients: Isobutyl alcohol: ORAL (LD50): Acute: 2460 mg/kg [Rat.]. DERMAL (LD50): Acute: 3400 mg/kg [Rabbit].

Section 3: Hazards Identification

Potential Acute Health Effects:

Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention.

Skin Contact:

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 415.56°C (780°F)

Flash Points: CLOSED CUP: 28°C (82.4°F). OPEN CUP: 37.7°C (99.9°F) (Cleveland).

Flammable Limits: LOWER: 1.2% UPPER: 10.9%

Products of Combustion: These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances:

Highly flammable in presence of open flames and sparks, of heat. Slightly flammable to flammable in presence of oxidizing materials. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Slightly explosive in presence of oxidizing materials.

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Special Remarks on Fire Hazards:

Vapor may travel considerable distance to source of ignition and flash back. Contact with strong oxidizers may cause fires. Ignites on contact with chromium oxide.

Special Remarks on Explosion Hazards: Contact with strong oxidizers may cause explosions.

Section 6: Accidental Release Measures

Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill:

Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.

Storage:

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 50 (ppm) from ACGIH (TLV) [United States] TWA: 152 (mg/m³) from ACGIH (TLV) [United States] TWA: 50 (ppm) [Canada] TWA: 152 (mg/m³) [Canada] TWA: 50 STEL: 75 (ppm) [United Kingdom (UK)] TWA: 154 STEL: 231 (mg/m³) [United Kingdom (UK)] TWA: 100 (ppm) from OSHA (PEL) [United States] TWA: 300 (mg/m³) from OSHA (PEL) [United States]³ Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Liquid.)

Odor: Sweetish and musty. Slightly suffocating

Taste: Sweet whiskey- like

Molecular Weight: 74.12g/mole

Color: Colorless.

pH (1% soln/water): Not available.

Boiling Point: 108°C (226.4°F)

Melting Point: -108°C (-162.4°F)

Critical Temperature: 274.6°C (526.3°F)

Specific Gravity: 0.806 @ 15 C (Water = 1)

Vapor Pressure: 1.2 kPa (@ 20°C)

Vapor Density: 2.56 (Air = 1)

Volatility: Not available.

Odor Threshold: 40 ppm

Water/Oil Dist. Coeff.: The product is more soluble in oil; $\log(\text{oil/water}) = 0.8$

Ionicity (in Water): Not available.

Dispersion Properties: See solubility in water, diethyl ether.

Solubility:

Miscible in alcohol or in diethyl ether. Partially soluble in cold water, hot water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, ignition sources, incompatibles

Incompatibility with various substances: Highly reactive with oxidizing agents.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Reacts with aluminum at 100 C to form explosive hydrogen gas.

Special Remarks on Corrosivity: Isobutyl will attack some forms of plastic, rubber, and coatings.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Absorbed through skin. Eye contact. Inhalation.

Toxicity to Animals:

Acute oral toxicity (LD50): 2460 mg/kg [Rat.]. Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit.].

Chronic Effects on Humans: MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast.

Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May cause cancer (tumorigenic) based on animal data. Passes through the placental barrier in human.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: Causes skin irritation. May be absorbed by the skin and affect the liver. Eyes: Causes eye irritation. Inhalation: May be harmful if inhaled. Causes respiratory tract and mucous membrane irritation. May also affect brain, behavior/Central Nervous system (CNS depressant with symptoms including headache, loss of coordination and judgement, dizziness, coma and death with exposure to large amounts), nausea. May also affect respiration (dyspnea). Ingestion: May be harmful if swallowed. May cause digestive tract irritation with nausea. May affect metabolism, blood, liver, behavior/Central nervous (symptoms similar to inhalation).

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: CLASS 3: Flammable liquid.

Identification: : Isobutyl Alcohol UNNA: 1212 PG: III

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information**Federal and State Regulations:**

Connecticut hazardous material survey.: Isobutyl alcohol Illinois toxic substances disclosure to employee act: Isobutyl alcohol Illinois chemical safety act: Isobutyl alcohol New York release reporting list: Isobutyl alcohol Rhode Island RTK hazardous substances: Isobutyl alcohol Pennsylvania RTK: Isobutyl alcohol Minnesota: Isobutyl alcohol Massachusetts RTK: Isobutyl alcohol Massachusetts spill list: Isobutyl alcohol New Jersey: Isobutyl alcohol New Jersey spill list: Isobutyl alcohol Louisiana spill reporting: Isobutyl alcohol California Director's List of Hazardous Substances: Isobutyl alcohol TSCA 8(b) inventory: Isobutyl alcohol TSCA 4(a) proposed test rules: Isobutyl alcohol TSCA 4(a) final test rules: Isobutyl alcohol TSCA 8(a) IUR: Isobutyl alcohol TSCA 8(d) H and S data reporting: Isobutyl alcohol TSCA 12(b) one time export: Isobutyl alcohol CERCLA: Hazardous substances.: Isobutyl alcohol: 5000 lbs. (2268 kg)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:**WHMIS (Canada):**

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC).

DSCL (EEC):

R10- Flammable. R36/38- Irritating to eyes and skin. S2- Keep out of the reach of children. S46- If swallowed, seek medical advice immediately and show this container or label.

HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 3

Reactivity: 0

Personal Protection: h

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 3

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

Section 16: Other Information

References:

-Hawley, G.G.. The Condensed Chemical Dictionary, 11e ed., New York N.Y., Van Nostrand Reinold, 1987. -Liste des produits purs t ratog nes, mutag nes, canc rog nes. R pertoire toxicologique de la Commission de la Sant  et de la S curit  du Travail du Qu bec. -Material safety data sheet emitted by: la Commission de la Sant  et de la S curit  du Travail du Qu bec. -SAX, N.I. Dangerous Properties of Industrial Materials. Toronto, Van Nostrand Reinold, 6e ed. 1984. -The Sigma-Aldrich Library of Chemical Safety Data, Edition II. -Guide de la loi et du r glement sur le transport des marchandises dangereuses au Canada. Centre de conformit  international Lt e. 1986.

Other Special Considerations: Not available.

Created: 10/10/2005 08:15 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.